



XKB Product features

Voltage: < 12V Current: < 20mA

Conduction time: 2ms

Closed circuit resistance: < 10ohm Open circuit resistance: > 10m ohm

High temperature resistance: 120 degrees

Terminal tension: 500gf / min

Humidity:25~95%RH

Service life: 100000 times

XKB Product features

XKB产品特性

- 1. SW-200m is a single ball type unidirectional tilt inductive trigger switch.
- 1、SW-200m为单球式单向倾斜感应触发开关。
- 2. When the guide end (no pin end) of the product is tilted and the tilt angle is greater than 10 degrees, the product is in the open circuit, (off) state. When the horizontal state of the product is tilted, the trigger end (gold-plated pin end) is lower than the horizontal and the tilt angle is greater than 10 degrees, the product is in the closed circuit, (on) state.
- 2.产品导向端(无销端)倾斜且倾斜角度大于10度时,产品处于开路(关)状态。当产品 水平状态倾斜,触发端(镀金销端)低于水平且倾斜角度大于10度时,产品处于闭路、
- 3. When it is placed horizontally, shaking is easy to trigger, but when there is no foot down, shaking is not easy to trigger.
- 3.水平放置时,摇动容易触发,但没有脚踩时,摇动不易触发。
- 4. The product of this specification is completely sealed, waterproof and dustproof.
- 4.本规范产品完全密封、防水、防尘。
- 5. Under normal conditions, the service life of the switch can reach 100000 times.
- 5.正常情况下, 开关使用寿命可达 10万次。
- 6. This product is made of environmental protection metal material.

1 DATE 1 CIA 1 CIA 100M 14(-15								6、本产	品采用环保金	属材料制	造。				
S Rubber stopper 1 LCP									6	Heat shr	inkable tube	1	PET		
***									(5)	Rubbe	er stopper	1			
② Guide needle B 1 Brass gold-plated ① ① Copper tube 1 Brass nickel ② ITEM PAPT NAMF QTY MATERIAL FINISHING REMARK DSND DATE SCALE: N/A MODEL TYPE: Ball switch						The second section of the	See the Condense Const	Control Science on	4	Rol	I Ball	1		silver	
DSND DATE SCALE: N/A AX AX AX AX AX AX BARK DESCRIPTION DATE DWG NO.: SW-200M-14G15 SW-200M-14G15 WEIGHT SHEET REVISION DATE DWG NO.: SW-200M-14G15 SW-200M-14G15 SW-200M-14G15 DATE DA					广	左目抽到上	一时八十	חם א דו	3	Guide	needle A	1	Brass		
E TIEM PAPT NAME QTY MATERIAL FINISHING REMARK DSND DATE SCALE: N/A AX AX AX AX AX AX AX AX AX						小生华村	以股份相	限公司	2	Guide	needle B	1	Brass		
DATE SCALE: N/A WIGHT TO BAll switch AX				1		12.7	1	Copper tube		1	Brass	nickel			
DSND DATE SCALE: N/A WOULD THE Ball switch AX		生 ITEM PAPT NAMF QT								QTY	MATERIA	L FINISHING	REMARK		
DATE VIEW: PART NO.: ΔX					- Z	文		The second second		DATE			SCALE: N/A	MODEL TYPE:	Ball switch
XX ±0.2mm	A V							DWN		DATE		,	VIEW:		
DESCRIPTION DATE REVISED APPROVED X.XXX ±0.05mm APPD DATE SIZE: A4 SW-200M-14G15 REVISIONS UNSPECIFIED TOLERANCES VKB INDUSTRIAL PRECISION COLUMITED WEIGHT SHEET REVISION						X.X	±0.2mm	CHKD		DATE		100000000000000000000000000000000000000	BEILD REVALUATION		
REVISIONS UNSPECIFIED TOLERANCES XKB INDUSTRIAL PRECISION CO. LIMITED WEIGHT SHEET REVISION	ΔX							ADDD		DATE			CIZE: A4	DWG NO.:	M 14015
YKB INDUSTRIAL PRECISION COLUMNIED	MARK	DESCRIPTION	DATE	REVISED	APPROVED			APPU		DATE		-	SIZE. A4		
www.xk-dg.cn www.helloxkb.com www.helloxkb.com www.helloxkb.com www.helloxkb.com language and la								XKB INDUSTRIAL PRECISION CO. LIMITE					IMITED		
		www.xk-dg.cn www.helloxkb.com	www.helloxkb.cn		A STATE OF THE PARTY OF			VIVD IIVI	JOSTRIAL	TILLU	OIOIV C	JO.,L	IIVIIIILD	1.0g 1/	A0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Vibration Sensors category:

Click to view products by XKB manufacturer:

Other Similar products are found below:

D7H-B2 D7H-A1 11031263-00 SCA1000-N1000070-004 LDTC-VERTICAL 11029997-00 11026275-00 SW-460-25N10G SW18015PZR-10G12B2 1005939-1 1005940-1 1007158-1 3-1004347-0 11032035-00 1767 2-1003744-0 3-1004346-0 1005447-1 1002794

1005935-1 1006015-1 2384 1-1002608-0 1-1003745-0 1-1004347-0 1-1002150-0 1-1002405-0 1-1002785-1 1-1002786-1 1-1002908-0 11003744-0 1-1004346-0 1-1004696-0 DT1-028K FDT1-052K DT2-028K DT1-052K D7A1 D7A2 VBS040100 VBS061100 VBS062100T

BU-23842-000 1001777 SEN-09197 D7S-A0001 2-1002908-0 2-1002145-0 2-1002150-0 2-1002608-0