







SPECIFICATIONS

Current Rating: 1.0 Amps
Withstanding Voltage: AC 500V
Insulation Resistance: 1000MΩ Min
Contact Resistance: 20mΩ Max
Operation Temperature: -40°C to +105°C
Insulator Material: Polyester (UL94V-0)
Contact Material: Phosphor bronze
Standard: PA6T
Contact Plating: Gold Flash
Max. Processing Temp: 240°C for 30-60 seconds
(260°C for 5 seconds)



RECOMMEND P.C.B LAYOUT
PCB TOLERANCE: ±0.05 (TOP VIEW)

P/N	PIN	DIM.A	DIM.B
FH1.27-01-01PZD	1	0.00	1.27
FH1.27-01-02PZD	2	1.27	2.54
FH1.27-01-03PZD	3	2.54	3.81
FH1.27-01-04PZD	4	3.81	5.08
FH1.27-01-05PZD	5	5.08	6.35
FH1.27-01-06PZD	6	6.35	7.62
FH1.27-01-07PZD	7	7.62	8.89
FH1.27-01-08PZD	8	8.89	10.16
FH1.27-01-09PZD	9	10.16	11.43
.....			
FH1.27-01-50PZD	50	(PIN-1)x1.27	(PIN)x1.27

PART NUMBER DESCRIPTION:

FH1.27-01-NPZD

(D=单排; S=双排)
(Z=直脚; W=弯脚)
(PIN数量; 01.....50PIN)
(排针开关)

MANUFACTURE DWG		 东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co., Ltd	
UNLESS OTHERWISE SPECIFIED TOLERANCES		TITLE: 1.27FH H4.3 1xNPIn 180度 W2.1 U型 PC2.4 6T	
DECIMALS:		PAR	FH1.27-01-NPZD
ANGLES:		DWN	
X.±0.30	X'±5'	CHKD	
X.X±0.20	X.X'±1'	APVD	
X.XX±0.10	X.XX'±0.5'	SCALE N:A	UNIT:MM
CUSTOMER COPY		SIZE:A4	SHEET:1F1
			REV:A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) ***category:***

Click to view products by [XUNPU](#) ***manufacturer:***

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [PCN6B-10P-2.5DS](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#)
[CSU011177004](#) [622-0430](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#)
[65817-010LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#)
[71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-43-024-10-001000](#)