






Plastic-Encapsulate Schottky Barrier Diode



FEATURE

- ◆High Current Capability
- ◆Low Forward Voltage Drop
- ◆Extremely Fast Switching Speed

Mechanical Data

- ◆SOT-323 Small Outline Plastic Package
- ◆Epoxy UL: 94V-0
- ◆Mounting Position: Any

Maximum Ratings & Thermal Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified.)





Parameters	Symbol	Value	Units
Maximum repetitive peak reverse voltage	V_{RRM}	30	V
Working Peak Reverse voltage	V_{RWM}	30	V
Maximum DC blocking voltage	V_{DC}	30	V
Maximum average forward rectified current	I_{FM}	200	mA
Peak forward surge current 8.3 ms single half sine-wave	I_{FSM}	600	mA
Typical thermal resistance	$R_{\theta JA}$	500	°C/W
Power Dissipation	P_D	200	mW
Junction Temperature	T_J	125	°C
Storage temperature range	T_{STG}	-50-+150	°C

Electrical Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified.)


Parameters	Symbol	Test Conditions	Min	Typ	Max	Units
Maximum forward voltage	V_{F1}	IF = 0.1mA			240	mV
	V_{F2}	IF = 1.0mA			320	
	V_{F3}	IF = 10mA			400	
	V_{F4}	IF = 30mA			500	
	V_{F5}	IF = 100mA			1000	
Maximum reverse breakdown voltage	V_R	IR=100uA	30			V
Maximum reverse current	I_R	VR=25V			2.0	uA
Type junction capacitance	C_j	VR = 1.0V, f = 1MHz			10	pF
Reverse Recovery time	t_{rr}	IF=IR=10mA Irr=0.1XIR, RL=100Ω			5	ns

Typical Characteristics




Package Outline

SOT-323



Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.200	0.400	0.008	0.016
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°

Precautions: PCB Design(Recommended land dimensions for SOT-323 diode. Electrode patterns for PCBs)



Note:
1. Controlling dimension; in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

Summary of Packing Options

Package	Package Description	Packing Quantity	Industry Standard
SOT-323	Tape/Reel, 7" reel	3000	EIA-481-1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Schottky Diodes & Rectifiers](#) category:

Click to view products by [YFW Electronics](#) manufacturer:

Other Similar products are found below :

[MA4E2039](#) [MMBD301M3T5G](#) [RB160M-50TR](#) [D83C](#) [RKS100KG#P1](#) [BAS 3010S-02LRH E6327](#) [BAT 54-02LRH E6327](#)
[NRVBAF360T3G](#) [NSR05F40QNX5G](#) [NTE555](#) [SB10-04A3-BT](#) [SBM30-03-TR-E](#) [SBS811-S-TL-E](#) [SBS818-TL-E](#) [SS3003CH-TL-E](#)
[STPS30S45CW](#) [GA01SHT18](#) [CRS10I30A\(Te85L,QM](#) [MBRB30H30CT-1G](#) [BAT 15-04R E6152](#) [IDL08G65C5](#) [JANTX1N5712-1](#) [SB007-](#)
[03C-TB-E](#) [SB10015M-TL-E](#) [NRVBB20100CTT4G](#) [NRVBM120LT1G](#) [NTSB30U100CT-1G](#) [STPS40SM100CG-TR](#) [CRG04\(T5L,TEMQ\)](#)
[ACDBA240-HF](#) [CDBQC0530L-HF](#) [STPS40SM120CTN](#) [NRVBM120ET1G](#) [STPS2545CGY-TR](#) [B160BQ-13-F](#) [SDM05U20CSP-7](#) [BAS 70-](#)
[07 E6433](#) [HSM560Je3/TR13](#) [HSM190Je3/TR13](#) [B330AF-13](#) [ACDBUC0230-HF](#) [MBR10200CTF-G1](#) [CDLL5712](#) [DMF2822-000](#) [VS-](#)
[50WQ04FNTRL-M3](#) [1N5817-G](#) [B350AF-13](#) [MF300A06F2](#) [SEMIX302KD16S](#) [5082-2835](#)