



	UL	IEC
1. Rated Voltage :	300V	320V
2. Rated Current :	15A	20A
3. Withstanding Voltage :	AC1600V/1Min.	
4. Operating Temperature :	-40°C~-105°C	
5. RoHS Compliance		
6. Safety Approval :	cULus CE	
7. "★" is the key quality control point		

① ② ③ ④ ⑤ ⑥

① Series NO. ④ 1 Single Pitch
 2 Double Pitch

② Pitch ⑤ Color: 1 Grey
 2 Blue
 3 Black
③ Poles 4 Green
02 02Contacts 5 Orange
03 03Contacts 6 Red
... 7 Transparent
24 24Contacts 8 Yellow
 9 White

⑥ Customer Request: 100--Standard

Total Pitch Tolerances in mm										Nominal dimension range in mm										$\perp$		$\div$		$-$		$//$	
over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over
0	30	53	70	90	115	150	250	350	500	0	30	53	70	90	115	150	200	250	320	0	10	all	all	0	100	100	150
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	10	all	all	to	to	to	to
30	53	70	90	115	150	250	350	500		30	53	70	90	115	150	200	250	320		10				100	150	100	150

				OPERATION		SCALE		Fit		 东莞市宇熙精密连接器有限公司 www.yxcon.com Dongguan Yuxi Electronic Co.,Ltd.		
				X.X	±0.25	UNIT		MM				
				X.XX	±0.20	SIZE	A4	DESIGN	赵文品2024.10.10	PART NO.	2EGTR-5.08-XXP-XX-100	
				X.XXX	±0.10							
				Angle	±3°	SHEET	1/1	CHECK		TITLE		
REV	DATE	SYMBOL	MODIFICATION DESCRIPTION	DIM	TOL	PROJ.		APPROVE		Customer No.		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [Yxcon](#) manufacturer:

Other Similar products are found below :

[57.510.0053](#) [721-104/026-047](#) [721-204/026-045](#) [ET02015000J0G](#) [860505](#) [860516](#) [GBPACX-12](#) [93.731.4953.0](#) [950-FB/03](#) [950-NLFL-DS/03](#) [PVS02-5,00](#) [1-1986160-3](#) [121-A-111/03](#) [121-A-111/05](#) [121-M-121/04](#) [121-M-211/03](#) [121-M-221/06](#) [1377680000](#) [1546228-5](#) [ELFP03110](#) [ELFT07250](#) [ELXH071G0E](#) [1725220000](#) [1760336](#) [1855000000](#) [19346](#) [1946309](#) [1973592](#) [2-1546857-6](#) [231-110/031-000](#) [25.320.4053.1](#) [25.320.4553.9](#) [25.320.4753.1](#) [25.340.0353.1](#) [25.340.1053.1](#) [25.345.3553.0M001](#) [25.640.3553.1](#) [931-HSL/03-HT](#) [950-FL-DS/04](#) [950-LH-DS/02](#) [950-NLFL-DS/06](#) [SH04-3,50](#) [SH08-5,08](#) [SH08-5,08-K](#) [SH12-5,08](#) [SH15-5,00](#) [SHS04-5,00](#) [30.303](#) [30.305](#) [30.306](#)