

Specifications

备注 (Remark)

1. 材料 (MATERIAL)

胶芯: PA6T+30%G.F UL94V-0, 颜色: 黑色.

Housing: PA6T+30%G.F UL94V-0, Color: Black

端子: 青铜, 镍底30u"MIN, 表面镀普金

Contact: bronze, GOLD PLATING OVER ALL

30u" MIN NICKEL UNDERPLATING OVER ALL

2. 特性 (characteristics):

额定电流: 2 AMP

Rating Current: 2 AMP.

接触阻抗: 20 mΩ MAX.

Contact Resistance: 20 mΩ MAX.

绝缘阻抗: 1000 MΩ MIN.





Insulating Resistance: 1000 MΩ MIN.

耐电压: AC 500V/分钟.

Withstanding Voltage: AC 500V/Minute.

温度范围: -40° C to +105° C

Temperture Range: -40° C to +105° C



Ordering Information

F243-12 02 A0 B WU C 1

NO. OF PINS
PER ROW
2-40P

Contact
Full of Gold

Plating
Semi-gold

INSULATOR
MATERIAL:

PACKING
A: PE Bag

A0=0.8u"

B0=0.8U'

B: PA6T

B: Tape & Reel

A1=1u"

B1=1U'

C: PA9T

C: Tube

A2=1.5u"

B2=1.5U'

D: LCP

D: Tube+CAP

A3=2u"

B3=2U'

E: Tray

A4=3u"

B4=3U'

A5=5u"

B5=5U'

A6=10u"

B6=10U'

A7=15u"

B7=15U'

A8=20u"

B8=20U'

A9=30u"

B9=30U'

S1=Ordinary Tin Plated

S2=Matte Tin Plated

S3=Tin-plated High-temperature

RoHS
COMPLIANT

客编:

注意事项

1. 带*为品质重点检验尺寸

OPERATION

SCALE

Fit

Yxcon

东莞市宇熙精密连接器有限公司

X.X ±0.25

UNIT

MM

www.yxcon.com

Dongguan Yuxi Electronic Co., Ltd.

X.XX ±0.20

SIZE

A4

DESIGN

李官森2022.08.05

PART NO.

F243-1202A0BWUC1

X.XXX ±0.10

SHEET

1/1

CHECK

TITLE

PH2.0*4.3 2*2P 蜈蚣脚 脚距6.0 塑宽=4.5 DIP:3.2

Angle ±3°

PRQJ.

Φ

APPROVE

Custoner No.

PA6T料 镀普金 126个/管装15根一扎

DIM TOL

A1 2022.08.05

△

更新图面

A0 2021.05.07

/

新版发行

REV DATE SYMBOL

MODIFICATION DESCRIPTION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) ***category:***

Click to view products by [Yxcon](#) ***manufacturer:***

Other Similar products are found below :

[892-18-020-10-001101](#) [0010894062](#) [0010977306](#) [0015477636](#) [0015917161](#) [0022104068](#) [0022121042](#) [0022155065](#) [0022281023](#) [57102-F02-18ULF](#) [PCN6B-10P-2.5DS](#) [58102-G61-06LF](#) [582553-1](#) [0015911208](#) [01.001.5753.1](#) [0022285048](#) [0050291907](#) [02.125.8002.8](#)
[CSU011177004](#) [622-0430](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#)
[65817-010LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#)
[71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-43-024-10-001000](#)